

DEVELOP

Dynamic balance

www.develop.eu



ineo+ 3070L



- > Colour SRA3+ digital press
- > Up to 3,823 pages per hour

Features that make all the difference!

These DEVELOP production systems target small to midsize commercial printers as well as in-house print rooms and Central Reprographic Departments (CRDs). As entry-level printing systems, they offer outstanding new features including scan & print to/from USB Flash, a dual colour highspeed scanner, and the possibility to manage print jobs directly from the operating panel. CRDs will find it easy to adapt to changing document workflows in the company, enhance their overall productivity, and to extend their range of products and services by offering new, sophisticated print products.

Durable performance

- > ineo+ 3070L
 - > Up to 71 A4 pages per minute
 - > Up to 36 SRA3 pages per minute
 - > Up to 3,823 A4 pages per hour
 - > Up to 1,951 SRA3 pages per hour
- > Enhanced overall scanning performance for scanning and copying
- > Features of the hotfolder, printer driver, imposition are enhanced for facilitated use
- > Enhanced work efficiency helps handle short turnaround jobs.

Ready-made print products

- > 20-sheet booklet making
- > 50-sheet stapling
- > For highest automation and enormous productivity
- > For more profit in the print room



Highest reliability

- > Long-life platform, long-lasting parts and consumables
- > Registration-swing mechanism for accurate duplex registration
- > Fusing-rolling mechanism
- > For prints with maximum efficiency
- > For lucrative short-run printing



Geared-up finishing

- > Letter fold-in
- > Stacking of up to 3,000 sheets
- > Optional 2- & 4-hole punching
- > Minimised human interaction

Environmentally sound

- > Robust and powerful despite the compact, lightweight body with fewer parts
- > Reduced power consumption with HD E toner
- > Industry-leading usage ratio of recycled PC and PET
- > For reduced environmental impact
- > Improved efficiency based on green values

Enhanced scanning performance

- > The dual scanner scans documents in one path
- > Double sheet detector
- > Max. 240 ipm (A4, 300 dpi)
- > Scanner capacity of 300 sheets



Perfect image quality

- > 1,200 x 1,200 dpi x 8 bit resolution (equivalent to 1,200 x 3,600 dpi)
- > HD E toner technology
- > For new print applications
- > For growing business

High-end print control

- > Flexible choice of controller technology: EFI® or own ineo controller
- > For intuitive operation
- > To save time and money



Ease of use

- > Automatic density balance adjustment
- > Open API/IWS support
- > Scan & print to USB Flash
- > Simple paper catalogue settings

Sophisticated media handling

- > New banner tray
- > Capable of feeding maximum 1,000 sheets of 762 mm long size in LU-202XLm
- > Banner size up to 1,300 x 330 mm
- > Envelope printing support
- > Banner duplex printing up to 762 x 330mm

Comprehensive media processing

- > Simplex & duplex printing on paper weights of up to 350 gsm
- > Envelope printing support
- > Supports a wide range of embossed papers
- > For highly flexible print products

Technical specifications

System specifications

Resolution	1,200 x 1,200 dpi x 8 bit 1,200 x 3,600 dpi equivalent
Paper weight	62–350 gsm
Duplex unit	Non-stack type; 62–350 gsm
Paper sizes	330 x 487 mm; 330 x 1.300 mm (optional)
Maximum image area	323 x 480 mm; 323 x 1,295 mm (Banner)
Paper input capacity	Standard: 1,500 sheets Max.: 4,250 sheets
Paper output capacity	Max.: 3,100 sheets
Main unit dimensions (W x D x H)	800 x 903 x 1,076 mm
Main unit weight	319 kg

Productivity

ineo+ 3070L	
A4 - max. per minute	71 ppm
A3 - max. per minute	39 ppm
SRA3 - max. per minute	36 ppm
A4 - max. per hour	3,823 pph
A3 - max. per hour	2,113 pph
SRA3 - max. per hour	1,951 pph

Controller

Internal ineo Controller	IC-605 A
Internal Fiery Controller	IC-417

Scanner specifications

Scan speed A4	Up to 240 ipm
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP; Scan-to-SMB; Scan-to-eMail
Scan formats	TIFF (single and multi page); PDF
Scan resolution	600 x 600 dpi

Copier specifications

Gradations	256 gradations
FCOT	Less than 8 sec. (colour A4)
Magnification	25–400%, in 0.1% steps
Mutiple copies	1–9,999

Accessories

Original cover	OC-511
Automatic document feeder	DF-706
Working table	WT-511
Heating unit for main body trays	HT-511
Heating unit for LU-202m/XL	HT-503
Bypass tray	MB-506
Booklet finisher	FS-612
Staple finisher	FS-531
2/4-hole punch kit for FS-612/531	PK-512
2-hole punch kit for FS-612/531	PK-513
Post inserter for FS-612/531	PI-502
Envelope fuser for FS-612/531	EF-103
Banner tray	MK-740
Banner tray for OT-510	MK-740m
Large capacity unit	LU-202m
Large capacity unit	LU-202XLm
High capacity output tray	OT-510
Output tray	OT-511
Envelope feeding kit	MK-746

DEVELOP

Konica Minolta Business Solutions Europe GmbH
Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 www.develop.eu

- All specifications refer to A4-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.